

C L A I M S

Sub A2

1. An appliance, comprising an indicating device; means forming an
2 outer surface provided with a throughgoing opening for receiving said indicating
3 device; means forming an edge region which surrounds said throughgoing
4 opening and is depressed relative to said outer surface, said edge region being
5 formed so that a decorative part is insertable in said edge region; and means
6 for releasably connecting said decorative part with said edge region.

1 2. An appliance as defined in claim 1, wherein said means for
2 releasably connecting is formed as an adhesive connection.

1 3. An appliance as defined in claim 2, wherein said adhesive
2 connection includes a double-sided adhesive band.

1 4. An appliance as defined in claim 2, wherein said decorative
2 part has a side facing toward said edge region and is provided at said side
3 with an adhesive surface which is self-adhesively connected with said edge
4 region, so as to form said ~~releasable connection~~
 releasably connecting means.

1 5. An appliance as defined in claim 1, wherein said decorative
2 part has a further throughgoing opening for receiving said indicating device.

1 6. An appliance as defined in claim 1, wherein said decorative
2 part has a plurality of additional throughgoing openings for receiving keys.

1 7. An appliance as defined in claim 5, wherein said decorative
2 part has a plurality of additional throughgoing openings for receiving keys.

1 8. An appliance as defined in claim 1, wherein said releasable
2 connection includes an arresting connection.

1 9. An appliance as defined in claim 8, wherein said arresting
2 connection includes an arresting projection provided on said decorative part
3 and an arresting opening provided on said edge region in which said
4 arresting projection is engageable.

1 10. An appliance as defined in claim 8, wherein said arresting
2 connection includes an arresting projection formed in said edge region, and
3 an arresting opening provided in said decorative part in which said arresting
4 projection is arrestable.

1 11. An appliance as defined in claim 1, wherein said
2 decorative part and said edge region are arranged so that a gap is provided

1 between said decorative part and said edge region for receiving a tool in
2 order to release said connection.

1 12. An appliance as defined in claim 1, wherein said edge
2 region is depressed in a two-step manner relative to said outer surface.

1 13. An appliance as defined in claim 12, wherein said edge
2 region has a deeper step which limits said throughgoing opening; and further
3 comprising a transparent disk which covers said indicating device and is
4 placed on said deeper step.

1 14. An appliance as defined in claim 12, wherein said edge
2 region has a higher step on which said decorative part is placed.

add
al